



U.S. Department of Energy
Energy Efficiency and Renewable Energy

federal energy management program

High Performance and Sustainable Buildings

A Historic Preservation Perspective

Don Horn, AIA, LEED AP
Director of Sustainable Design

GSA

U.S. General Services Administration
Public Buildings Service



Memorandum of Understanding

Federal Leadership in High Performance and Sustainable Buildings

- Signed January 24, 2006 by 21 individuals representing 17 agencies and over 95% of all Federal buildings



Federal Government Commitment

- . . . to designing, locating, constructing, maintaining, and operating its facilities in an
 - energy efficient and sustainable manner that
 - strives to achieve a balance that will realize
 - high standards of living,
 - wider sharing of life's amenities,
 - maximum attainable reuse and recycling of depletable resources, in an
 - economically viable manner,
 - consistent with Department and Agency missions.



MOU Goals

- Reduce the total ownership costs of facilities;
- Improve energy efficiency and water conservation;
- Provide safe, healthy, and productive built environments; and,
- Promote sustainable environmental stewardship.



I. Employ Integrated Design Principles

- Integrated Design.
 - Initiates and maintains an integrated project team
 - Establishes performance goals
 - Considers all stages of the building's lifecycle



U.S. Department of Energy
Energy Efficiency and Renewable Energy

I. Employ Integrated Design Principles





I. Employ Integrated Design Principles

- Commissioning.
 - Employ total building commissioning practices . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

I. Employ Integrated Design Principles





II. Optimize Energy Performance

- Energy Efficiency.
 - Establish a whole building performance target that takes into account the intended use, occupancy . . .
 - For new construction, reduce the energy cost budget by 30 percent . . .
 - For major renovations, reduce the energy cost budget by 20 percent . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

II. Optimize Energy Performance





U.S. Department of Energy
Energy Efficiency and Renewable Energy

II. Optimize Energy Performance





II. Optimize Energy Performance

- Measurement and Verification.
 - . . . install building level utility meters in new major construction and renovation projects . . .
 - . . . measure all new major installations using Energy Star . . .
 - Enter data and lessons learned from sustainable buildings into the High Performance Buildings Database



U.S. Department of Energy
Energy Efficiency and Renewable Energy

II. Optimize Energy Performance





III. Protect and Conserve Water

- Indoor Water.
 - Employ strategies that in aggregate use a minimum of 20 percent less . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

III. Protect and Conserve Water





III. Protect and Conserve Water

- Outdoor Water.
 - Use water efficient landscape and irrigation strategies . . . to reduce outdoor potable water consumption by a minimum of 50 percent . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

III. Protect and Conserve Water





IV. Enhance Indoor Environmental Quality

- Ventilation and Thermal Comfort.
 - Meet the current ASHRAE Standard 55 . . .
and ASHRAE Standard 62.1 . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

IV. Enhance Indoor Environmental Quality






IV. Enhance Indoor Environmental Quality

- Moisture Control.
 - Establish and implement a moisture control strategy . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

IV. Enhance Indoor Environmental Quality





IV. Enhance Indoor Environmental Quality

- Daylighting.
 - Achieve a minimum daylight factor . . .
 - Provide automatic dimming controls or accessible manual lighting controls . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

IV. Enhance Indoor Environmental Quality





IV. Enhance Indoor Environmental Quality

- Low-Emitting Materials.
 - Specify materials and products with low pollutant emissions . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

IV. Enhance Indoor Environmental Quality





IV. Enhance Indoor Environmental Quality

- Protect Indoor Air Quality during Construction.
 - Follow . . . Indoor Air Quality Guidelines for Occupied Buildings under Construction . . .
 - After construction and prior to occupancy, conduct a minimum 72-hour flush-out . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

IV. Enhance Indoor Environmental Quality





V. Reduce Environmental Impact of Materials

- Recycled Content.
 - . . . use products meeting or exceeding EPA's recycled content recommendations . . .



V. Reduce Environmental Impact of Materials

- Biobased Content.
 - . . . use products meeting or exceeding USDA's biobased content recommendations
 - . . . use biobased products made from rapidly renewable resources and certified sustainable wood products.



U.S. Department of Energy
Energy Efficiency and Renewable Energy

V. Reduce Environmental Impact of Materials






V. Reduce Environmental Impact of Materials

- Construction Waste.
 - During a project's planning stage, identify local recycling and salvage operations recycle or salvage at least 50 percent construction, demolition and land clearing waste



V. Reduce Environmental Impact of Materials





U.S. Department of Energy
Energy Efficiency and Renewable Energy

V. Reduce Environmental Impact of Materials





V. Reduce Environmental Impact of Materials

- Ozone Depleting Compounds.
 - Eliminate the use of ozone depleting compounds . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

V. Reduce Environmental Impact of Materials





MOU & LEED

Integrated Design.

- EA p1 – Fundamental Commissioning
- EA 3 – Enhanced Commissioning 1 pt.

Optimize Energy Performance.

- EA 1 – Optimize Energy Performance 5 pt.

Protect and Conserve Water.

- WE 3.1 – Water Use Reduction 1 pt.
- WE 1.1 – Water Efficient Landscaping 1 pt.



MOU & LEED

Enhance Indoor Environmental Quality.

- EQ 7.1 – Thermal Comfort 1 pt.
- EQ p1 – Minimum IAQ Performance
- EQ 8.1 – Daylight and Views: Daylight 75% of Spaces 1 pt.
- EQ 4.1 – Low-Emitting Materials: Adhesives & Sealants 1 pt.
- EQ 4.2 – Low-Emitting Materials: Paints & Coatings 1 pt.
- EQ 4.3 – Low-Emitting Materials: Carpet Systems 1 pt.
- EQ 3.1 – Construction IAQ Management Plan: During Construction 1 pt.

Reduce Environmental Impact of Materials.

- MR 2.1 – Construction Waste Management: Divert 50% 1 pt.
- EA p3 – Fundamental Refrigerant Management
- EA 4 – Enhanced Refrigerant Management 1 pt.

16 pt.



Financing Historic Federal Buildings


An Analysis of Current Practice

- GSA Draft Report, May 1999
- Overall, the operating costs per rentable square foot for historic buildings were 10 percent less than non-historic buildings. The cleaning costs were 9 percent less. The maintenance costs were 10 percent less. The utility costs were 27 percent less.



Financing Historic Federal Buildings


Figure 9 - Utility Cost 1998





Financing Historic Federal Buildings


Figure 10 - Utility Costs of Compared to Industry Standard 1998





Financing Historic Federal Buildings


Figure 14 - Efficiency of Buildings Compared to Utility Costs 1998





U.S. Department of Energy
Energy Efficiency and Renewable Energy


Ariel Rios Building Washington, DC





U.S. Department of Energy
Energy Efficiency and Renewable Energy

Howard M. Metzenbaum U.S. Courthouse Cleveland, OH





U.S. Department of Energy
Energy Efficiency and Renewable Energy

Howard M. Metzenbaum U.S. Courthouse





U.S. Department of Energy
Energy Efficiency and Renewable Energy


Scowcroft Building Ogden, UT





U.S. Department of Energy
Energy Efficiency and Renewable Energy

Scowcroft Building





GSA LEED Registered Historic Buildings

- John McCormack Building, Boston, MA
- Martin Luther King, Jr. Federal Building, Atlanta, GA
- Potter Stewart U.S. Courthouse, Cincinnati, OH
- 536 S. Clark, Chicago, IL
- Federal Building/U.S. Courthouse, Davenport, IA
- U.S. Courthouse, Little Rock, AR
- William Nakamura U.S. Courthouse, Seattle, WA
- Mary Switzer Building, Washington, DC
- Main Department of the Interior, Washington, DC
- Eisenhower Executive Office Building, Washington, DC
- Herbert Hoover Building, Washington, DC
- Lafayette Building, Washington, DC
- 1800 F Street, Washington, DC
- . . .



U.S. Department of Energy
Energy Efficiency and Renewable Energy

GSA Building Washington, DC





U.S. Department of Energy
Energy Efficiency and Renewable Energy

GSA Building





U.S. Department of Energy
Energy Efficiency and Renewable Energy


GSA Building





U.S. Department of Energy
Energy Efficiency and Renewable Energy



Eisenhower Executive Office Building Washington, DC





U.S. Department of Energy
Energy Efficiency and Renewable Energy

Embodied Energy





Life-Cycle Assessment




Exhibit 1-1. Life Cycle Stages (Source: EPA, 1993)



Life-Cycle Assessment Approach

- Define the scope
- Consider energy, materials, emissions
- The historic building is already there
- No upstream profile for historic building



U.S. Department of Energy
Energy Efficiency and Renewable Energy

Sustainable Design =

Good Design

Historic Preservation =

Good Maintenance



U.S. Department of Energy
Energy Efficiency and Renewable Energy



Don Horn
909 First Ave.
Room 411
Seattle, WA 98103
206-220-4944
donald.horn@gsa.gov