Southwest Research Institute

APBF-DEC DEER Conference

Low Emissions Potential of EGR-SCR-DPF and Advanced Fuel Formulations-*A Progress Report*

Department of Emissions Research
Automotive Products and Emissions Research Division

August 2002

Acknowledgments

Southwest Research Institute wishes to acknowledge the following organizations, agencies, trade associations, and companies for their support of this work and their many technical contributions without which progress in this project would not have been possible:

- US DOE-Funding Via ORNL
- U.S. EPA
- API-Fuels
- NPRA
- EMA
- MECA
- Battelle-Fluids
- CARB/SCAQMD
- Technical Team

Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

Introduction--APBF-DEC



Adapted From NREL/W. Clark Presentation 9/26/01

Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

Objectives

- To Demonstrate Low Emissions Performance of Advanced Diesels+LPL EGR*+Urea SCR+DPF (2 Different Systems)
- To Determine The Regulated And Unregulated Emissions W. &W/O Emission Controls
- To Examine The Emission Control System Durability
- To Sample Toxic Emissions For Analysis By Outside Lab
- To Evaluate Sensitivities of The Control System Performance To Fuel Variables

Emissions Goals: 2007 EPA HDE Standards

** Low Pressure Loop EGR*

Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

Technical Approach--Development (ƒ 1)



*30 ppm for occasional verification

Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

Test Setup


AIR FILTER
EGR COOLER
LPL EGR
T (IMP)
N
TPS
UREA INJECTION
CB-DPF AR
SCR AR
CLEANUP CATALYST
EXHAUST FLOW SENSORS
FLOW BALANCING VALVES
INTAKE THROTTLE
EGR VALVE
EXHAUST
CB-DPF AL
SCR AL
EXHAUST DAMPER
LPL EGR PICKUP
EXHAUST MANIFOLD
ATA AFTERCOOLER
C12 DIESEL ENGINE
UREA INJECTION
UREA INJECTION CONTROL
UREA
PRESSURE CONTROL
UREA PUMP
INTAKE MANIFOLD

Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

System Components--Engine

Engine Description (on consignment to the project)

- Caterpillar C12
- 12.0 L/450 hp
- In-Line/6 Cylinders
- Turbocharged/Intercooled
- Rated Speed: 1800 rpm
- Peak Torque: 1650 lb-ft
- Peak Torque Speed:1200 rpm
- Emission Calibration: MY 2000

System Components--Fuels

- **Fuel 1:** Baseline --3 ppm S
- **Fuel 2:** Durability/Emission Eval. --8 ppm S
- **Fuel 3:** Research/Emission Eval.--15 ppm S
- **Fuel 4:** BP 15
- **Fuel 5:** 30 ppm (Excursions)

Fuel Estimates

- *Phase 1: Development 25,000 To 30,000 Gallons*
- *Phase 2: 6.5 Gallons/OICA--2 OICAs/Hr.--13 Gallons/Hr. or 78,000 Gallons Per 6,000 Hours*

Engine Installation -- EGR System

Exhaust Treatment Arrangement--CB-DPF and SCR



Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions

Engine Performance



Transient Emissions--350ppm Cert. 2D Fuel



Steady-State Emissions--350ppm Cert. 2D Fuel



EGR* Calibration



EGR : Low Pressure Loop EGR With CB-DPF*

Transient Emissions--EGR* and DECSE 3ppm Fuel



EGR* : Low Pressure Loop EGR With CB-DPF

Steady-State Emissions Comparison--As-Received W. Cert. Fuel 350ppm S and W.EGR*--DECSE 3ppm Fuel



EGR* : Low Pressure Loop EGR With CB-DPF

Transient Emissions--EGR*/SCR/DPF/DECSE 3ppm Fuel



* *HD Standards For 2007

EGR* : Low Pressure Loop EGR With CB-DPF

Steady-State Emissions Emissions Comparison--

As Received vs. EGR*/CB-DPF/SCR--DECSE 3ppm Fuel

Preliminary-Without Cleanup Catalyst



EGR : Low Pressure Loop EGR With CB-DPF*

Steady-State Emissions--DEVELOPMENT & PROGRESS



Outline

- Introduction
- Objectives
- Technical Approach
- Test Setup
- System Components
- Results
- Summary & Conclusions



Summary and Conclusions

- The C-12 Caterpillar test engine had an EPA Transient NOx/PM emissions of 3.5/0.07 g/bhp-hr.
- The LPL EGR system was installed and calibrated to yield:
  - over 50% NOx reduction and,
  - about 90%PM reduction
- System A SCR was installed and urea injection was optimized for the OICA cycle.
- System A (including LPL EGR) yielded NOx/PM of 0.17/0.003 g/bhp-hr in the OICA test.
- System A calibration for the EPA transient test cycle is in progress and nearing completion.
- System B calibration will follow the completion of System A calibration.
- Preparation for the durability phase of the program is complete.
- Both durability engines have been broken in.

Some Conclusions Were Based on Preliminary Results

S
W
R
I
L
R