

Bellingham Bay Builders

La Pedrera Net Zero Residence | Anacortes, WA | bellinghambaybuilders.com













PROJECT DATA

• Layout: 2 bdrm, 2 bath, 1 fl, 1,592 ft²

Climate: IECC 4C, coldCompleted: January 2020

• Category: Custom for Buyer <3,000 ft²

MODELED PERFORMANCE DATA

- **HERS Index:** without PV 42; with PV -8
- Annual Energy Costs: (vs typical new homes) without PV \$1,200; with PV \$350
- Annual Energy Cost Savings: without PV \$1,200; with PV \$2,000
- Annual Energy Savings: without PV 7,100 kWh; with PV 16,500 kWh
- Savings in the First 30 Years: without PV \$50,300; with PV \$84,000

CONTACT

Dave Brogan 360-733-7500 dave@bellinghambaybuilders.com

KEY FEATURES

- Walls: 2x6, 24" o.c., advanced framed, R-32.6 total: R-24 fiberglass, 2-stud corners, coated OSB, liquid flashing, 2" R-8.6 mineral wool, 1x4 furring, cedar and metal siding.
- Roof: Shed roof, 24-gauge standing-seam metal roof, ENERGY STAR Cool Roof certified.
- Attic: Unvented attic R-66 total: 14" TJI rafters, with R-51 fiberglass batt, no overhang, topped with $\frac{1}{2}$ " coated OSB, sealed at roof-wall seam, topped with 2x6 rafters with 24" overhang, with 3.5" R-15 fiberglass batts then 2" air gap and $\frac{1}{2}$ " plywood sheathing.
- Foundation: Insulated crawlspace, 6 mil. vapor barrier to sill plate, 3" concrete slab. 2" EPS exterior insulation with $\frac{1}{2}$ " fiber cement protection board.
- Windows: Double-pane, argon-filled, low-e2, fiberglass composite or aluminum-clad wood casement, awning, and fixed frames. U=0.24, SHGC=0.27 to 0.32, tuned to direction.
- Air Sealing: 0.78 ACH 50. Roof-to-wall coated sheathing, liquid flashing at all seams.
- Ventilation: HRV continuous.
- HVAC: Ductless and ducted mini-split heat pumps, 12.2 HSPF, 36.0 SEER. Passive solar.
- Hot Water: Heat pump water heater, 2.90 EF, 50-gal., exhaust ducted outside, to Smart recirc.
- Lighting: 100% LED, motion sensors, daylighting.
- Appliances: ENERGY STAR dishwasher, clothes washer, heat pump ventless clothes dryer.
- Solar: 8.51-kW PV system; 23 370-W panels.
- Water Conservation: Low-flow fixtures. drought-resistant landscaping, rain barrels.
- Energy Management System: Programmable thermostats, PV tracking.
- Other: Electric vehicle charging station, Accessibility features, High-recycled-content metal siding & roofing. Recycled fir timbers in porch roofs. No-VOC paints & finishes.





